

| Type   | Interflow CF 61/61                              | Interflow CF 61/76                              | Interflow CF 61/91                              | Interflow CF 61/122                             |
|--|---|---|---|---|
| Material unit  | HPL   | HPL   | HPL   | HPL   |
| Material worktop   | Stainless steel 304                             | Stainless steel 304                             | Stainless steel 304                             | Stainless steel 304                             |
| Material worktop   | Stainless steel 316 optional                    | Stainless steel 316 optional                    | Stainless steel 316 optional                    | Stainless steel 316 optional                    |
| Material workspace   | Top stainless steel 304 /<br>Workspace HPL      | Top stainless steel 304 /<br>Workspace HPL      | Top stainless steel 304 /<br>Workspace HPL      | Top stainless steel 304 /<br>Workspace HPL      |
| Dim. external body (wxdxh)                                 | 640 x 792 x 1144 mm                             | 792 x 792 x 1144 mm                             | 946 x 792 x 1144 mm                             | 1250 x 792 x 1144 mm                            |
| Dim. workspace (wxdxh)                                     | 616 x 547 x 616 mm                              | 768 x 547 x 616 mm                              | 922 x 547 x 616 mm                              | 1226 x 547 x 616 mm                             |
| Installation fits through door of                          | 800 mm  | 800 mm  | 800 mm  | 800 mm  |
| Height worktop w.r.t. floor                                | 760 / 940 mm (sit-/standing)                    | 760 / 940 mm (sit-/standing)                    | 760 / 940 mm (sit-/standing)                    | 760 / 940 mm (sit-/standing)                    |
| Total height including frame /<br>sit/standing             | 1884 / 2064 mm                                  | 1884 / 2064 mm                                  | 1884 / 2064 mm                                  | 1884 / 2064 mm                                  |
| Weight (top cabinet)                                       | 80 kg   | 90 kg   | 110 kg  | 140 kg  |
| Electric high-low frame                                    | Optional  | Optional  | Optional  | Optional  |
| One-piece workspace  | Yes   | Yes   | Yes   | Yes   |
| Full service front/top side                                | Yes   | Yes   | Yes   | Yes   |
| Fan type   | Direct current motor                            | Direct current motor                            | Direct current motor                            | Direct current motor                            |
| Voltage  | 230 V / 50 Hz                                   | 230 V / 50 Hz                                   | 230 V / 50 Hz                                   | 230 V / 50 Hz                                   |
| Fuse   | 16 A  | 16 A  | 16 A  | 16 A  |
| Electricity consumption                                    | 1,1 A   | 1,2 A   | 1,3 A   | 1,4 A   |
| Power consumption  | 150 W / Total of the unit<br>including lighting | 160 W / Total of the unit<br>including lighting | 170 W / Total of the unit<br>including lighting | 180 W / Total of the unit<br>including lighting |
| Brightness   | > 1000 Lux - dimmable                           | > 1000 Lux - dimmable                           | > 1000 Lux - dimmable                           | > 1000 Lux - dimmable                           |
| Lighting type  | LED - dimmable                                  | LED - dimmable                                  | LED - dimmable                                  | LED - dimmable                                  |
| Control  | Touchscreen /<br>PLC technology                 | Touchscreen /<br>PLC technology                 | Touchscreen /<br>PLC technology                 | Touchscreen /<br>PLC technology                 |
| Socket 230 V   | Optional  | Optional  | Optional  | Optional  |
| Side windows   | Optional  | Optional  | Optional  | Optional  |
| Connectivity-package                                       | Optional  | Optional  | Optional  | Optional  |
| Weighing balance facilities<br>integrated into the worktop | Optional  | Optional  | Optional  | Optional  |
| Acoustic level   | 47 dB(A)  | 47 dB(A)  | 47 dB(A)  | 47 dB(A)  |
| Ergonomic leg space  | Yes   | Yes   | Yes   | Yes   |
| Ergonomic seat angle 12 degr.                              | Yes   | Yes   | Yes   | Yes   |
| Complies with GMP-class A                                  | Yes   | Yes   | Yes   | Yes   |
| Complies with NEN-EN-ISO 14644-1                           | Yes   | Yes   | Yes   | Yes   |
| Crossflow NEN-EN-ISO 14644-1 /<br>GMP                      | 0,25 – 0,50 / 0,36 – 0,54 m/s                   | 0,25 – 0,50 / 0,36 – 0,54 m/s                   | 0,25 – 0,50 / 0,36 – 0,54 m/s                   | 0,25 – 0,50 / 0,36 – 0,54 m/s                   |
| Warranty   | 1 year  | 1 year  | 1 year  | 1 year  |
| Customer specific requirements                             | Negotiable / own factory                        | Negotiable / own factory                        | Negotiable / own factory                        | Negotiable / own factory                        |
| <b>Filter grade</b>  |   |   |   |   |
| Pre-filter, NEN-EN-ISO 16890                               | G4  | G4  | G4  | G4  |
| Absolute filter, EN1822                                    | H14   | H14   | H14   | H14   |

| Type   | Interflow CF 61/152                             | Interflow CF 61/183                             | Interflow CF 61/244                             | Interflow CF 76/61                              |
|--|---|---|---|---|
| Material unit  | HPL   | HPL   | HPL   | HPL   |
| Material worktop   | Stainless steel 304                             | Stainless steel 304                             | Stainless steel 304                             | Stainless steel 304                             |
| Material worktop   | Stainless steel 316 optional                    | Stainless steel 316 optional                    | Stainless steel 316 optional                    | Stainless steel 316 optional                    |
| Material workspace   | Top stainless steel 304 /<br>Workspace HPL      | Top stainless steel 304 /<br>Workspace HPL      | Top stainless steel 304 /<br>Workspace HPL      | Top stainless steel 304 /<br>Workspace HPL      |
| Dim. external body (wxdxh)                                 | 1554 x 792 x 1144 mm                            | 1860 x 792 x 1144 mm                            | 2500 x 792 x 1144 mm                            | 640 x 792 x 1296 mm                             |
| Dim. workspace (wxdxh)                                     | 1530 x 547 x 616 mm                             | 1836 x 547 x 616 mm                             | 2476 x 547 x 616 mm                             | 616 x 547 x 768 mm                              |
| Installation fits through door of                          | 800 mm  | 800 mm  | 800 mm  | 800 mm  |
| Height worktop w.r.t. floor                                | 760 / 940 mm (sit/standing)                     | 760 / 940 mm (sit/standing)                     | 760 / 940 mm (sit/standing)                     | 760 / 940 mm (sit/standing)                     |
| Total height including frame /<br>sit/standing             | 1884 / 2064 mm                                  | 1884 / 2064 mm                                  | 1884 / 2064 mm                                  | 2036 / 2216 mm                                  |
| Weight (top cabinet)                                       | 160 kg  | 175 kg  | 275 kg  | 90 kg   |
| Electric high-low frame                                    | Optional  | Optional  | Optional  | Optional  |
| One-piece workspace  | Yes   | Yes   | Yes   | Yes   |
| Full service front/top side                                | Yes   | Yes   | Yes   | Yes   |
| Fan type   | Direct current motor                            | Direct current motor                            | Direct current motor                            | Direct current motor                            |
| Voltage  | 230 V / 50 Hz                                   | 230 V / 50 Hz                                   | 230 V / 50 Hz                                   | 230 V / 50 Hz                                   |
| Fuse   | 16 A  | 16 A  | 16 A  | 16 A  |
| Electricity consumption                                    | 1,5 A   | 1,6 A   | 3,5 A   | 1,2 A   |
| Power consumption  | 190 W / Total of the unit<br>including lighting | 200 W / Total of the unit<br>including lighting | 350 W / Total of the unit<br>including lighting | 160 W / Total of the unit<br>including lighting |
| Brightness   | > 1000 Lux - dimmable                           | > 1000 Lux - dimmable                           | > 1000 Lux - dimmable                           | > 1000 Lux - dimmable                           |
| Lighting type  | LED - dimmable                                  | LED - dimmable                                  | LED - dimmable                                  | LED - dimmable                                  |
| Control  | Touchscreen /<br>PLC technology                 | Touchscreen /<br>PLC technology                 | Touchscreen /<br>PLC technology                 | Touchscreen /<br>PLC technology                 |
| Socket 230 V   | Optional  | Optional  | Optional  | Optional  |
| Side windows   | Optional  | Optional  | Optional  | Optional  |
| Connectivity-package                                       | Optional  | Optional  | Optional  | Optional  |
| Weighing balance facilities<br>integrated into the worktop | Optional  | Optional  | Optional  | Optional  |
| Acoustic level   | 47 dB(A)  | 47 dB(A)  | 47 dB(A)  | 47 dB(A)  |
| Ergonomic leg space  | Yes   | Yes   | Yes   | Yes   |
| Ergonomic seat angle 12 degr.                              | Yes   | Yes   | Yes   | Yes   |
| Complies with GMP-class A                                  | Yes   | Yes   | Yes   | Yes   |
| Complies with NEN-EN-ISO 14644-1                           | Yes   | Yes   | Yes   | Yes   |
| Crossflow NEN-EN-ISO 14644-1 /<br>GMP                      | 0,25 – 0,50 / 0,36 – 0,54 m/s                   | 0,25 – 0,50 / 0,36 – 0,54 m/s                   | 0,25 – 0,50 / 0,36 – 0,54 m/s                   | 0,25 – 0,50 / 0,36 – 0,54 m/s                   |
| Warranty   | 1 year  | 1 year  | 1 year  | 1 year  |
| Customer specific requirements                             | Negotiable / own factory                        | Negotiable / own factory                        | Negotiable / own factory                        | Negotiable / own factory                        |
| <b>Filter grade</b>  |   |   |   |   |
| Pre-filter, NEN-EN-ISO 16890                               | G4  | G4  | G4  | G4  |
| Absolute filter, EN1822                                    | H14   | H14   | H14   | H14   |

| Type   | Interflow CF 76/76                              | Interflow CF 76/91                              | Interflow CF 76/122                             | Interflow CF 76/152                             |
|--|---|---|---|---|
| Material unit  | HPL   | HPL   | HPL   | HPL   |
| Material worktop   | Stainless steel 304                             | Stainless steel 304                             | Stainless steel 304                             | Stainless steel 304                             |
| Material worktop   | Stainless steel 316 optional                    | Stainless steel 316 optional                    | Stainless steel 316 optional                    | Stainless steel 316 optional                    |
| Material workspace   | Top stainless steel 304 /<br>Workspace HPL      | Top stainless steel 304 /<br>Workspace HPL      | Top stainless steel 304 /<br>Workspace HPL      | Top stainless steel 304 /<br>Workspace HPL      |
| Dim. external body (wxdxh)                                 | 792 x 792 x 1296 mm                             | 946 x 792 x 1296 mm                             | 1250 x 792 x 1296 mm                            | 1554 x 792 x 1296 mm                            |
| Dim. workspace (wxdxh)                                     | 768 x 547 x 768 mm                              | 922 x 547 x 768 mm                              | 1226 x 547 x 768 mm                             | 1530 x 547 x 768 mm                             |
| Installation fits through door of                          | 800 mm  | 800 mm  | 800 mm  | 800 mm  |
| Height worktop w.r.t. floor                                | 760 / 940 mm (sit/standing)                     | 760 / 940 mm (sit/standing)                     | 760 / 940 mm (sit/standing)                     | 760 / 940 mm (sit/standing)                     |
| Total height including frame /<br>sit/standing             | 2036 / 2216 mm                                  | 2036 / 2216 mm                                  | 2036 / 2216 mm                                  | 2036 / 2216 mm                                  |
| Weight (top cabinet)                                       | 100 kg  | 120 kg  | 150 kg  | 165 kg  |
| Electric high-low frame                                    | Optional  | Optional  | Optional  | Optional  |
| One-piece workspace  | Yes   | Yes   | Yes   | Yes   |
| Full service front/top side                                | Yes   | Yes   | Yes   | Yes   |
| Fan type   | Direct current motor                            | Direct current motor                            | Direct current motor                            | Direct current motor                            |
| Voltage  | 230 V / 50 Hz                                   | 230 V / 50 Hz                                   | 230 V / 50 Hz                                   | 230 V / 50 Hz                                   |
| Fuse   | 16 A  | 16 A  | 16 A  | 16 A  |
| Electricity consumption                                    | 1,5 A   | 1,6 A   | 1,8 A   | 3,0 A   |
| Power consumption  | 190 W / Total of the unit<br>including lighting | 200 W / Total of the unit<br>including lighting | 220 W / Total of the unit<br>including lighting | 290 W / Total of the unit<br>including lighting |
| Brightness   | > 1000 Lux - dimmable                           | > 1000 Lux - dimmable                           | > 1000 Lux - dimmable                           | > 1000 Lux - dimmable                           |
| Lighting type  | LED - dimmable                                  | LED - dimmable                                  | LED - dimmable                                  | LED - dimmable                                  |
| Control  | Touchscreen /<br>PLC technology                 | Touchscreen /<br>PLC technology                 | Touchscreen /<br>PLC technology                 | Touchscreen /<br>PLC technology                 |
| Socket 230 V   | Optional  | Optional  | Optional  | Optional  |
| Side windows   | Optional  | Optional  | Optional  | Optional  |
| Connectivity-package                                       | Optional  | Optional  | Optional  | Optional  |
| Weighing balance facilities<br>integrated into the worktop | Optional  | Optional  | Optional  | Optional  |
| Acoustic level   | 47 dB(A)  | 47 dB(A)  | 47 dB(A)  | 47 dB(A)  |
| Ergonomic leg space  | Yes   | Yes   | Yes   | Yes   |
| Ergonomic seat angle 12 degr.                              | Yes   | Yes   | Yes   | Yes   |
| Complies with GMP-class A                                  | Yes   | Yes   | Yes   | Yes   |
| Complies with NEN-EN-ISO 14644-1                           | Yes   | Yes   | Yes   | Yes   |
| Crossflow NEN-EN-ISO 14644-1 /<br>GMP                      | 0,25 – 0,50 / 0,36 – 0,54 m/s                   | 0,25 – 0,50 / 0,36 – 0,54 m/s                   | 0,25 – 0,50 / 0,36 – 0,54 m/s                   | 0,25 – 0,50 / 0,36 – 0,54 m/s                   |
| Warranty   | 1 year  | 1 year  | 1 year  | 1 year  |
| Customer specific requirements                             | Negotiable / own factory                        | Negotiable / own factory                        | Negotiable / own factory                        | Negotiable / own factory                        |
| <b>Filter grade</b>  |   |   |   |   |
| Pre-filter, NEN-EN-ISO 16890                               | G4  | G4  | G4  | G4  |
| Absolute filter, EN1822                                    | H14   | H14   | H14   | H14   |

| Type   | Interflow CF 76/183                             | Interflow CF 76/244                             | Interflow CF 91/91                              | Interflow CF 91/122                             |
|--|---|---|---|---|
| Material unit  | HPL   | HPL   | HPL   | HPL   |
| Material worktop   | Stainless steel 304                             | Stainless steel 304                             | Stainless steel 304                             | Stainless steel 304                             |
| Material worktop   | Stainless steel 316 optional                    | Stainless steel 316 optional                    | Stainless steel 316 optional                    | Stainless steel 316 optional                    |
| Material workspace   | Top stainless steel 304 /<br>Workspace HPL      | Top stainless steel 304 /<br>Workspace HPL      | Top stainless steel 304 /<br>Workspace HPL      | Top stainless steel 304 /<br>Workspace HPL      |
| Dim. external body (wxdxh)                                 | 1860 x 792 x 1296 mm                            | 2500 x 792 x 1296 mm                            | 964 x 824 x 1449 mm                             | 1250 x 824 x 1449 mm                            |
| Dim. workspace (wxdxh)                                     | 1836 x 547 x 768 mm                             | 2476 x 547 x 768 mm                             | 922 x 547 x 921 mm                              | 1226 x 547 x 921 mm                             |
| Installation fits through door of                          | 800 mm  | 800 mm  | 810 mm  | 810 mm  |
| Height worktop w.r.t floor                                 | 760 / 940 mm (sit/standing)                     | 760 / 940 mm (sit/standing)                     | 760 / 940 mm (sit/standing)                     | 760 / 940 mm (sit/standing)                     |
| Total height including frame /<br>sit/standing             | 2036 / 2216 mm                                  | 2036 / 2216 mm                                  | 2189 / 2369 mm                                  | 2189 / 2369 mm                                  |
| Weight (top cabinet)                                       | 195 kg  | 300 kg  | 150 kg  | 170 kg  |
| Electric high-low frame                                    | Optional  | Optional  | Optional  | Optional  |
| One-piece workspace  | Yes   | Yes   | Yes   | Yes   |
| Full service front/top side                                | Yes   | Yes   | Yes   | Yes   |
| Fan type   | Direct current motor                            | Direct current motor                            | Direct current motor                            | Direct current motor                            |
| Voltage  | 230 V / 50 Hz                                   | 230 V / 50 Hz                                   | 230 V / 50 Hz                                   | 230 V / 50 Hz                                   |
| Fuse   | 16 A  | 16 A  | 16 A  | 16 A  |
| Electricity consumption                                    | 3,2 A   | 3,5 A   | 2,2 A   | 2,9 A   |
| Power consumption  | 310 W / Total of the unit<br>including lighting | 350 W / Total of the unit<br>including lighting | 350 W / Total of the unit<br>including lighting | 450 W / Total of the unit<br>including lighting |
| Brightness   | > 1000 Lux - dimmable                           | > 1000 Lux - dimmable                           | > 1000 Lux - dimmable                           | > 1000 Lux - dimmable                           |
| Lighting type  | LED - dimmable                                  | LED - dimmable                                  | LED - dimmable                                  | LED - dimmable                                  |
| Control  | Touchscreen /<br>PLC technology                 | Touchscreen /<br>PLC technology                 | Touchscreen /<br>PLC technology                 | Touchscreen /<br>PLC technology                 |
| Socket 230 V   | Optional  | Optional  | Optional  | Optional  |
| Side windows   | Optional  | Optional  | Optional  | Optional  |
| Connectivity-package                                       | Optional  | Optional  | Optional  | Optional  |
| Weighing balance facilities<br>integrated into the worktop | Optional  | Optional  | Optional  | Optional  |
| Acoustic level   | 47 dB(A)  | 47 dB(A)  | 47 dB(A)  | 47 dB(A)  |
| Ergonomic leg space  | Yes   | Yes   | Yes   | Yes   |
| Ergonomic seat angle 12 degr.                              | Yes   | Yes   | Yes   | Yes   |
| Complies with GMP-class A                                  | Yes   | Yes   | Yes   | Yes   |
| Complies with NEN-EN-ISO 14644-1                           | Yes   | Yes   | Yes   | Yes   |
| Crossflow NEN-EN-ISO 14644-1 /<br>GMP                      | 0,25 – 0,50 / 0,36 – 0,54 m/s                   | 0,25 – 0,50 / 0,36 – 0,54 m/s                   | 0,25 – 0,50 / 0,36 – 0,54 m/s                   | 0,25 – 0,50 / 0,36 – 0,54 m/s                   |
| Warranty   | 1 year  | 1 year  | 1 year  | 1 year  |
| Customer specific requirements                             | Negotiable / own factory                        | Negotiable / own factory                        | Negotiable / own factory                        | Negotiable / own factory                        |
| <b>Filter grade</b>  |   |   |   |   |
| Pre-filter, NEN-EN-ISO 16890                               | G4  | G4  | G4  | G4  |
| Absolute filter, EN1822                                    | H14   | H14   | H14   | H14   |

| Type  | Interflow CF 91/152                          | Interflow CF 91/183                          | Interflow CF 91/244                          |
|---|--|--|--|
| Material unit   | HPL  | HPL  | HPL  |
| Material worktop  | Stainless steel 304                          | Stainless steel 304                          | Stainless steel 304                          |
| Material worktop  | Stainless steel 316 optional                 | Stainless steel 316 optional                 | Stainless steel 316 optional                 |
| Material workspace                                      | Top stainless steel 304 /<br>Workspace HPL   | Top stainless steel 304 /<br>Workspace HPL   | Top stainless steel 304 /<br>Workspace HPL   |
| Dim. external body (wxdxh)                              | 1554 x 824 x 1449 mm                         | 1860 x 824 x 1449 mm                         | 2500 x 824 x 1449 mm                         |
| Dim. workspace (wxdxh)                                  | 1530 x 547 x 921 mm                          | 1836 x 547 x 921 mm                          | 2476 x 547 x 921 mm                          |
| Installation fits through door of                       | 810 mm                                       | 810 mm                                       | 810 mm                                       |
| Height worktop in relation to floor                     | 760 / 940 mm (sit/standing)                  | 760 / 940 mm (sit/standing)                  | 760 / 940 mm (sit/standing)                  |
| Total height including frame / sit/standing             | 2189 / 2369 mm                               | 2189 / 2369 mm                               | 2189 / 2369 mm                               |
| Weight (top cabinet)                                    | 195 kg                                       | 220 kg                                       | 350 kg                                       |
| Electric high-low frame                                 | Optional                                     | Optional                                     | Optional                                     |
| One-piece workspace                                     | Yes  | Yes  | Yes  |
| Full service front/top side                             | Yes  | Yes  | Yes  |
| Fan type  | Direct current motor                         | Direct current motor                         | Direct current motor                         |
| Voltage   | 230 V / 50 Hz                                | 230 V / 50 Hz                                | 230 V / 50 Hz                                |
| Fuse  | 16 A   | 16 A   | 16 A   |
| Electricity consumption                                 | 3,6 A  | 3,9 A  | 4,4 A  |
| Power consumption                                       | 550 W / Total of the unit including lighting | 650 W / Total of the unit including lighting | 750 W / Total of the unit including lighting |
| Brightness  | > 1000 Lux - dimmable                        | > 1000 Lux - dimmable                        | > 1000 Lux - dimmable                        |
| Lighting type   | LED - dimmable                               | LED - dimmable                               | LED - dimmable                               |
| Control   | Touchscreen / PLC technology                 | Touchscreen / PLC technology                 | Touchscreen / PLC technology                 |
| Socket 230 V  | Optional                                     | Optional                                     | Optional                                     |
| Side windows  | Optional                                     | Optional                                     | Optional                                     |
| Connectivity-package                                    | Optional                                     | Optional                                     | Optional                                     |
| Weighing balance facilities integrated into the worktop | Optional                                     | Optional                                     | Optional                                     |
| Acoustic level  | 47 dB(A)                                     | 47 dB(A)                                     | 47 dB(A)                                     |
| Ergonomic leg space                                     | Yes  | Yes  | Yes  |
| Ergonomic seat angle 12 degr.                           | Yes  | Yes  | Yes  |
| Complies with GMP-class A                               | Yes  | Yes  | Yes  |
| Complies with NEN-EN-ISO 14644-1                        | Yes  | Yes  | Yes  |
| Crossflow NEN-EN-ISO 14644-1 / GMP                      | 0,25 – 0,50 / 0,36 – 0,54 m/s                | 0,25 – 0,50 / 0,36 – 0,54                    | 0,25 – 0,50 / 0,36 – 0,54                    |
| Warranty  | 1 year                                       | 1 year                                       | 1 year                                       |
| Customer specific requirements                          | Negotiable / own factory                     | Negotiable / own factory                     | Negotiable / own factory                     |
| <b>Filter grade</b>                                     |  |  |  |
| Pre-filter, NEN-EN-ISO 16890                            | G4   | G4   | G4   |
| Absolute filter, EN1822                                 | H14  | H14  | H14  |

## Interflow

De Stek 15  
1771 SP Wieringerwerf  
Nederland  
T +31 (0)227 60 28 44  
E [info@interflow.nl](mailto:info@interflow.nl)  
W [www.interflow.nl](http://www.interflow.nl)

## Want to know more about the possibilities?

Please contact our advisor:

Arjan van der Scheer  
M +31 (0)653 54 12 05  
E [arjan.vander.scheer@interflow.nl](mailto:arjan.vander.scheer@interflow.nl)

