

| Type | Interflow DAK 60 | Interflow DAK 90 | Interflow DAK 120 | Interflow DAK 150 | Interflow DAK 180 |
|---|---------------------------------|---------------------------------|---------------------------------|---------------------------------|---------------------------------|
| Material cabinet | HPL | HPL | HPL | HPL | HPL |
| Material worktop | Trespa Toplab | Trespa Toplab | Trespa Toplab | Trespa Toplab | Trespa Toplab |
| Materiaal workspace | HPL | HPL | HPL | HPL | HPL |
| Dim. external body (wxdxh) | 640 x 750 x 1144 mm | 900 x 750 x 1144 mm | 1200 x 750 x 1144 mm | 1500 x 750 x 1144 mm | 1800 x 750 x 1144 mm |
| Dim. workspace (wxdxh) | 616 x 525 x 800 mm | 876 x 525 x 800 mm | 1176 x 525 x 800 mm | 1476 x 525 x 800 mm | 1776 x 525 x 800 mm |
| Installation fits through 800 mm door | Yes | Yes | Yes | Yes | Yes |
| Height worktop in relation to the floor | Standing height 950 mm | Standing height 950 mm | Standing height 950 mm | Standing height 950 mm | Standing height 950 mm |
| Height of work opening | 416 mm | 416 mm | 416 mm | 416 mm | 416 mm |
| Weight (top cabinet) | 75 kg | 90 kg | 115 kg | 150 kg | 175 kg |
| One-piece workspace | Yes | Yes | Yes | Yes | Yes |
| Window positions | 60 / 416 mm | 60 / 416 mm | 60 / 416 mm | 60 / 416 mm | 60 / 416 mm |
| Exhaust air (inflow) | 275 m ³ /h (0,3 m/s) | 400 m ³ /h (0,3 m/s) | 525 m ³ /h (0,3 m/s) | 660 m ³ /h (0,3 m/s) | 800 m ³ /h (0,3 m/s) |
| Extract air connection opening | Ø 160 mm | Ø 160 mm | Ø 160 mm | Ø 200 mm | Ø 250 mm |
| Inflow speed A118 | 0,25 – 0,40 m/s | 0,25 – 0,40 m/s | 0,25 – 0,40 m/s | 0,25 – 0,40 m/s | 0,25 – 0,40 m/s |
| Fan type | Not applicable | Not applicable | Not applicable | Not applicable | Not applicable |
| Voltage | 230 V / 50 Hz | 230 V / 50 Hz | 230 V / 50 Hz | 230 V / 50 Hz | 230 V / 50 Hz |
| Fuse | 16 A | 16 A | 16 A | 16 A | 16 A |
| Electricity consumption | 0,1 A | 0,11 A | 0,17 A | 0,2 A | 0,2 A |
| Power consumption | 10 W | 10 W | 16 W | 25 W | 20 W |
| Brightness | > 400 Lux | > 400 Lux | > 400 Lux | > 400 Lux | > 400 Lux |
| Lighting type | LED | LED | LED | LED | LED |
| Control | On/off light switch | On/off light switch | On/off light switch | On/off light switch | On/off light switch |
| Socket 230 V | Optional | Optional | Optional | Optional | Optional |
| Side windows | Optional | Optional | Optional | Optional | Optional |
| Optic flow indicator | Optional | Optional | Optional | Optional | Optional |
| Ergonomic seat angle 12 degrees | Yes | Yes | Yes | Yes | Yes |
| A118 (labour inspection) | Yes | Yes | Yes | Yes | Yes |
| Warranty | 1 year | 1 year | 1 year | 1 year | 1 year |
| Customer-specific requirements | Negotiable / own factory | Negotiable / own factory | Negotiable / own factory | Negotiable / own factory | Negotiable / own factory |

Interflow

De Stek 15
1771 SP Wieringerwerf
Nederland
T +31 (0)227 60 28 44
E info@interflow.nl
W www.interflow.nl

Want to know more about the possibilities?

Please contact our advisor:

Arjan van der Scheer
M +31 (0)653 54 12 05
E arjan.vander.scheer@interflow.nl